

Cerniera per porte "Compatta" tre ali

Cerniera registrabile a tre ali in alluminio. La registrazione avviene senza dover sfilare l'anta sia mediante la rotazione delle due boccole eccentriche alle due estremità, sia sulla boccola centrale, in questo caso mediante apposito chiavino ns. art. 06890.00.00. Il sistema di sicurezza

antiefrazione è posto sia sul perno (per mezzo di un anello antisfilamento) che sui carter copriviti, grazie ad uno spinotto da 5 mm.

Portata di 2 cerniere Kg 130

DOTAZIONI

- 2 tappi in nylon
- 6 viti TCEI 8MAx20 in acciaio inox
- 6 boccole di fissaggio in acciaio
- 3 spinotti antiefrazione da mm 5 inox
- 1 grano 5MAx5 inox
- 2 riscontri in all. completi di molle per

- il fissaggio
- 1 perno antisfilamento mm 11 in acciaio inox
- 3 boccole registrabili in bisolfuro di molibdeno
- 3 viti 4MA inox per fissaggio carter



3 wing hinge for "Compatta" doors

Adjustable three-wing hinge, made from steel. You can adjust it without having to dismantle the hinge, both by rotating the two eccentric bushes at the two ends, and on the central bush, in this case through the suitable key, our art. 06890.00.00. The break-in security system is positioned on

both the pin (using a slip-proof ring) and the screw guards, using a 5 mm gudgeon pin.

Capacity of 2 hinges, Kg. 130

DOTAZIONI

- 2 aluminium check plates equipped with securing springs
- 1 stainless steel slip-proof pin, 11 mm
- 3 adjustable molybdenum bisulphate bushes
- 3 screws for securing the guard 4MA

- 2 nylon stoppers
- 6 stainless steel TCEI 8MA x 20 screws
- 6 steel securing bushes
- 3 stainless steel break-in gudgeon pins, 5 mm
- 1 stainless steel 5MAx5 grub screws

art.08200.00.00



- 4 pezzi / 4 units

art.08210.00.00



- 4 pezzi / 4 units

